

YOUR
SMART
ENERGY



Additional
energy use



Longer
service life



SMILE-G3-T4/T5/T6/T8/T10

HOME SERIES

POWER

4 / 5 / 6 / 8 / 10 kW

CAPACITY

3.65 kWh modular
expandable up to 43.8 kWh

3.8 kWh modular
expandable up to 22.8 kWh

4.56 kWh modular
expandable up to 27.36 kWh

9.3 kWh modular
expandable up to 111.6 kWh



LUMIT[®]
Versicherung

Munich RE



reddot design award 2022



GOOD DESIGN AWARD



HYBRID BATTERY

Optimal capacity utilization through pack balancing

100% charge/discharge power at 1C

High reliability through Multi-BMS system

Safe lithium iron phosphate (LFP) cells

Performance warranty up to 25 years

5-year all-risk insurance (optional)

HYBRID INVERTER

UPS capability

Price signaling capability

Wall or floor mounting

Anti-shading function

3x MPPTs optimal for flexible roof
orientation

Smart Home Ready

SMILE-G3-T4/T5/T6/T8/T10



Model	SMILE-G3-T4	SMILE-G3-T5	SMILE-G3-T6	SMILE-G3-T8	SMILE-G3-T10
System Specifications					
Nominal Output Power	4 kW	5 kW	6 kW	8 kW	10 kW
Usable Capacity Range	3.65 - 43.8 kWh / 3.8 - 22.8 kWh / 4.56 - 27.36 kWh / 9.3 - 111.6 kWh				
Battery Chemistry	LFP (LiFePO4)				
Warranty	10 Years Product Warranty, 10 Years Battery Performance Warranty				

Inverter Technical Specifications					
Model	SMILE-G3-T4-INV	SMILE-G3-T5-INV	SMILE-G3-T6-INV	SMILE-G3-T8-INV	SMILE-G3-T10-INV
Coupling	Hybrid	Hybrid	Hybrid	Hybrid	Hybrid
Max.PV Input Power	8 kW	10 kW	12 kW	16 kW	20 kW
Max.PV Input Current	16 A / 16 A / 16 A				
Max.PV Input Voltage	1,000 V				
MPPT Number / Strings per MPPT	3 / 1				
MPPT Voltage Range	140 ~ 950 V				
Max.PV Short-Circuit Current	24 A / 24 A / 24 A				
Max.Charging/Discharging Current	40 A				
Max.Charging/Discharging Power	4 kW	5 kW	6 kW	8 kW	10 kW
Nominal Frequency	50 / 60 Hz				
Nominal Voltage	220 V / 380 V, 230 V / 400 V				
Phase	Three Phase				
Nominal Output Power (Grid Port)	4 kW	5 kW	6 kW	8 kW	10kW
Nominal Output Power (Backup Port)	4 kW	5 kW	6 kW	8 kW	10 kW
Nominal Input Power(on-grid)	8 kW	10 kW	12 kW	16 kW	20 kW
Backup	UPS				
Communication	Ethernet / WiFi / Modbus / API				
Relative Humidity	0 ~ 90% (No Condensation)				
Dimensions(WxDxH)	610 × 212.5 × 416 mm				
Weight	26.7 kg				
Ingress Protection	IP65				
Safety	IEC 62109-1/-2				
EMC	IEC 61000-6-1/-2/-3/-4, IEC 61000-3-11, EN 61000-3-12				
Grid Regulation	VDE 4105, EN 50549-1, VDE 0126-1-1, NC RFG, Tor Erzeuger, CEI 0-21, C10/I1				
Overvoltage Category	DC Type II according to EN / IEC 61643				
Cooling	Controlled Ventilator				
Noise	≤ 39 dB				
Maximum/European Efficiency	97.6 % / 96.8 %				

Battery Technical Specifications				
Model	SMILE-G3-BAT-3.8S	SMILE-G3-BAT-4.0S	SMILE-G3-BAT-4.5S	SMILE-G3-BAT-9.3S
Nominal Capacity	3.8 kWh	4.0 kWh	4.56 kWh	9.3 kWh
Usable Capacity	3.65 kWh	3.8 kWh	4.56 kWh	9.3 kWh
Depth of Discharge (DoD)	95 % *	95 % *	100 % *	100 % *
Nominal Voltage	96 V	96 V	96 V	96 V
Max. Charging/Discharging Current	40 A	42 A	50 A	52.5 A
Operating Temperature Range	-10°C ~ 50 °C **	-10°C ~ 60 °C **	-20 °C ~ 50 °C **	-20 °C ~ 50 °C **
Cycle Life	10,000 ***	10,000 ***	10,000 ***	10,000 ***
Modular Connection	1 ~ 6,8,10,12 ****	1 ~ 6	1 ~ 6	1 ~ 6,8,10,12 ****
IP Protection	IP21	IP65	IP65	IP65
Dimensions (W x D x H)	610 × 212.5 × 435 mm	610 × 212.5 × 435 mm	610 × 212.5 × 435 mm	610 × 210 × 634 mm
Weight	39.2 kg	42.5 kg	53 kg	81 kg
Noise	≤ 35 dB	≤ 25 dB	≤ 35 dB	≤ 35 dB
Fire-Fighting	Aerosol	N/A	Aerosol	Aerosol

* Test condition: Max. 0.5C charge/discharge at 25±2°C.

** Performance reduction may occur depending on the state of charge and temperature. Optimal operating temperature 15°C ~ 30°C.

*** Under specific test conditions.

**** Maximum 6 Batteries for each cluster in series, up to 2 clusters in parallel.



Alpha ESS Co., Ltd.
☎ +86 513 8060 6891
✉ info@alpha-ess.com
🌐 www.alphaess.com
📍 No. 1086, Bihua Road,
Nantong Hi-Tech Zone,
Jiangsu Province, China

Alpha ESS Italy S.r.l.
☎ +39 339 462 4288
✉ info@alphaess.it
🌐 www.alphaess.com
📍 Via Del Molinuzzo 83,
59100 Prato (PO), Italy

Alpha ESS Europe GmbH
☎ +49 610 3459 1601
✉ europe@alpha-ess.de
🌐 www.alphaess.de
📍 Horizon Tower 17.0G
Alfred-Herrhausen-Allee 3-5
65760 Eschborn, Germany

Alpha ESS UK Ltd.
☎ +44 0330 043 2610
✉ info@alpha-ess.com
📍 Drake house, Long street,
Dursley, GL11 4HH UK

Alpha ESS Australia Pty. Ltd.
☎ +61 02 9000 7676
✉ techsupport@alphaess.au
🌐 www.alphaess.com
📍 8/15-21 Gibbs Street,
Chatswood,
NSW 2067 Australia

Alpha ESS USA, Inc.
☎ +1 408 368 7828
✉ usa@alpha-ess.com
📍 Unit 5 2180 S Ivanhoe St,
Denver, CO 80222 USA

Alpha ESS International Pte. Ltd.
☎ +65 6513 1125 / +65 6513 1126
✉ Singapore@alpha-ess.com
📍 2 Corporation Road #01-06A
Corporation Place 618494
Singapore

Alpha ESS Korea Co., Ltd.
✉ info@alpha-ess.com
📍 2F, 19-4, Nohyeong 11-gil,
Jeju-si, Jeju-do, Republic
of Korea

Alpha ESS South Africa (Pty.) Ltd.
✉ measservice@alpha-ess.com
📍 La Rocca Office Park, Block
B1 321 Main Road, Bryanston,
Johannesburg, 2191